



1. Copy XP-80 driver files to the desktop as shown below.

Xprinter[®]芯/缉

2.Right-click the Desktop, select OPEN Terminal, and switch to the Desktop directory with the cd command, as shown below. The US dollar symbol will show Desktop. If the system is in Chinese, it may show Desktop.





3.With the ls command, check to see if the driver file is in the current directory, and if there are no surprises, you will see XP-80 appear in the list.

	000			
File Edit View Search Terminal	Help			
<pre>ljq@ubuntu:~\$ ls Desktop Downloads Documents examples.desktop ljq@ubuntu:~\$ cd ~/Desktop/ ljq@ubuntu:~/Desktop\$ ls XP-80 ljq@ubuntu:~/Desktop\$</pre>	Music Pictures	Public snap	Templates Videos	

4.To install the driver, use root and sudo su command to switch to root. Enter sudo su command and press enter. The password is not visible.

root@ubu	intu: /home/lj	q/Desktop	
File Edit View Search Terminal Help			
<pre>ljq@ubuntu:~\$ ls Desktop Downloads Music Documents examples.desktop Pictur ljq@ubuntu:~\$ cd ~/Desktop/ ljq@ubuntu:~/Desktop\$ ls XP-80 ljq@ubuntu:~/Desktop\$ sudo su [sudo] password for ljq: root@ubuntu:/home/ljq/Desktop#</pre>	Public es snap	Templates Videos	

5.To change the 777 permissions of the driver, the command is as follows.

ro	ot@ubuntu: /l	home/ljq	/Desktop (900
File Edit View Search Terminal H	Help			
ljq@ubuntu:~\$ ls Desktop Downloads Documents examples.desktop ljq@ubuntu:~\$ cd ~/Desktop/ ljq@ubuntu:~/Desktop\$ ls XP-80	Music P Pictures s	Public Snap	Templates Videos	
<pre>ljq@ubuntu:~/Desktop\$ sudo su [sudo] password for ljq: root@ubuntu:/home/ljq/Desktop root@ubuntu:/home/ljq/Desktop</pre>	u p# chmod 777 p#	7 XP-80	-	



6.Enter./XP-80, then press Enter, noting that the previous point is also entered.

root@ubuntu: /home/ljq/Desktop 🛛 👄 🔿 😣
File Edit View Search Terminal Help root@ubuntu:/home/ljq/Desktop# ./XP-80 Xprinter cupsdrv-2.4.0 installer
Models included: XP-80
64 Linux Searching for ServerRoot, ServerBin, and DataDir tags in /etc/cups/cupsd.conf
ServerBin tag not present in cupsd.conf - using default
DataDir tag not present in cupsd.conf - using default
ServerRoot = ServerBin = DataDir =
11 44 Restarting CUPS [.ok] Stopping cups (via systemctl): cups.service. [.ok] Starting cups (via systemctl): cups.service.
Go to http://localhost:631, or http://127.0.0.1:631 to manage your printer plea

To this display driver has been installed successfully, prompt the driver to open the url, the next is to add a printer.

7.Open your browser, input http://127.0.0.1:631 in the address bar, and press enter. Adding Printers and Classes as shown in the figure below.





8.Enter Administration, click Add Printer, as shown below.

Administration - Administration - Administration - CUPS 2 × +	- CUPS 2.2.7 - Mozilla Firefox 🛛 🖨 🖨 🤅
$\leftarrow \rightarrow$ C' \bigtriangleup (i) localhost:631/adm	nin ···· 🖂 🕅 » =
CUPS.org Home Administration	Classes Help Jobs Printers
Administration	
Drinton	Comren
Printers	Server
Add Printer Find New Printers	Edit Configuration File View Access Log
Manage Printers	View Error Log View Page Log
	Server Settings:
Classes	Advanced >
	Share printers connected to this system
Add Class Manage Classes	Allow printing from the Internet
	 Use Kerberos authentication (FAQ)
Jobs	Allow users to cancel any job (not just their
	own) Save debugging information for
CLPS and the CLPS loop are trademarks of Annia Inc. Converted	2007 2017 Annie Inc. All antist reservert

9.A login box may pop up. Please enter the login user and password.

	Authentication Required	
and the second	http://127.0.0.1:631 is requesting your username and password. The	site says: "CUPS"
User Name:	ljq	
Password:	[+	
	Cancel	ок



10.After entering the login user and password, click OK, jump to the following screen, select the Local Printers that you want, and click Continue.

Add I	Printer - CUPS 2.2.7	- Mozilla	a Firefox	1			
Add Printer - CUPS 2.2.7 × +							
← → C ^I	:631/admin/			⊠ ☆	111	»	Ξ
CUPS.org Home Admini	stration Classes	Help	Jobs	Printers			
Add Printer							
Local Printers:	CUPS-BRF (Virt	ual Brail	le BRF	Printer)			
	Serial Port #1	_	-	Serial port			
	Serial Port #2						
Parallel port	Upl #1			LICD sorts			
	UNKNOWN	D)		USB ports			
Network Port		P)					
Discovered Network Printers							
Discovered Network Printers.							
Other Network Printers:	Backend Error H	andler	0.0.2				
	Internet Printing	rotocol	(http)				
	Internet Printing I	rotocol	(ipps)				
	Internet Printing I	rotocol	(ipp)				
	Internet Printing I	rotocol	(nttps)				
	LPD/LPR Host of	Printer					
	AppSocket/HP J	etDirect					
	Continue						
		- 10 1000 cm	1947 - A				_
CUPS and the CUPS logo are trademarks of Apple In	c. Copyright © 2007-2017 App	ile Inc. All rig	ghts reserved	i.			

Suppose Local Printers select Serial Port #1, set the same value to the Serial Port configuration of the printer, and then click Continue, as shown below.

Add Printer - Cl	JPS 2.2.7	× 🕑 New Tab	COPS 2.2.7		+	×		e	
€) → C @	(i)	127.0.0.1:631/adr	nin			… ⊠ ☆	III \	»	Ξ
CUPS.org	Home	Administration	Classes	Help	Jobs	Printers			
Add Print	er								
Connection:	serial:/dev	//ttyS0?baud=11	5200						
Parity:	19200 ×]							
	0.14								
Data Bits:	8 ~								
Data Bits: Flow Control:	None	~							
Data Bits: Flow Control:	None Continu	•							
Data Bits: Flow Control:	None Continu	e							



If Local Printers select HP Printer (HPLIP), set it according to the Printer's IP configuration.

Socket://IP address: IP port, then click Continue, as shown below.



11. Below you can fill in the driver name you want, otherwise you can leave blank, then click Continue.





12. Make select XP, and then click Continue.

	Add Printer - C	CUPS 2.2.7 -	Mozill	a Firefo	x			0
Add Printer - CUPS 2.2.7	🗙 🧉 New Tab		×	+				
← → ♂ ଢ 0	127.0.0.1:631/adm	in			⊠ ☆	111	»	≡
CUPS.org Home	Administration	Classes	Help	Jobs	Printers			
Description: Location: Connection: Sharing:	usb://Unknown/Pri Do Not Share This	inter s Printer						
Make:	Star Tally Tektronix Texas Instruments Toshiba TOSHIBA TEC Corp Xante Xerox							
	Zebra							
	Continue							
Or Provide a PPD File:	Browse No f	ile selected						
	Add Printer							
CUPS and the CUPS logo are trademar	is of Apple Inc. Copyright ©	2007-2017 Appl	e Inc. All ri	ghts reserve	ed.	_		

Then enter the following interface, select XP-80 (EN) for Model, and click Add Printer.

	Add Print	er - CUPS 2.2.7	- Mozilla I	Firefox		000
Add Printer - CUPS 2.2.7 🗙	赵 New	Tab	× -	+		
← → C ŵ ③ 12	27.0.0.1:631,	/admin		🛛 t	2 111	» =
CUPS.org Home A	Administrati	on Classes	Help 、	Jobs Printers		
Name: XF Description: Location: Connection: us Sharing: Do Make: xp	2-80-USB b://Unknow o Not Share	n/Printer This Printer	anufacture	Pr		
Model: 🗙	2-80 (en)					
Or Provide a PPD File:	Browse Add Printer	No file selected	e Inc. All right	ts reserved.		



13. Enter the following interface, select the driver Settings you want, and click Set Default Options.

Image: Set Printer Options - Corr 2 Image: New Yab Image: New Ya	Set Driptor	Options Cill	Set Printer Optio	ons - CUPS 2	2.2.7 - M	ozilla Fi	refox		0	• •
CUPS.org Home Administration Classes Help Jobs Printers Set Printer Options Set Default Options for XP-80-USB Set Default Options Cash Drawer Control Buzzer Control Logo General Cut Options Cash Drawer Control Buzzer Control Logo General Media Size: 80(72mm) * 210mm Set Default Options Set Default Options	←) → C ^a		127.0.0.1:631/adr	nin			⊠ ☆	lii\	»	≡
Set Printer Options Set Default Options for XP-80-USB <u>General</u> Cut Options Cash Drawer Control Buzzer Control Logo Control Banners Policies <u>General</u> <u>Media Size:</u> 80(72mm) * 210mm ~ <u>Set Default Options</u>	CUPS.	org Home	Administration	Classes	Help	Jobs	Printers			
General Cut Options Cash Drawer Control Buzzer Control Logo General Media Size: 80(72mm) * 210mm ~ Set Default Options Set Default Options	Set P Set Def	rinter ault Opt	Options	2-80-US	в					-
General Media Size: 80(72mm) * 210mm ~ Set Default Options	General Control	Cut Opti Banners	ons Cash D Policies	rawer Co	ontrol	Buz	zer Control	Log	jo	_
Set Default Options			Madia	General				-		
			Set	Default Op	(72mm) *	* 210mm				

Next, the printer has been added successfully, as shown below. Click the name of the printer or wait for a moment to enter the printer management page.

		Set Printer Optio	ns - CUPS 2	.2.7 - M	ozilla Fi	refox				• 😣
🚥 Set Printer Opti	ons - CUP	🗙 👩 New Tab		×	+					
€ → C @	0	127.0.0.1:631/adr	nin			🖂 י	☆	111	»	≡
CUPS.org	Home	Administration	Classes	Help	Jobs	Printers	5			

Set Printer Options

Set Default Options for XP-80-USB

Printer XP-80-USB default options have been set successfully.



14. Click the management page of the printer and print the test page as shown below.



· 20 H 8 0



Xprinter[®] 达烊

60 words, 412 characters

Page 1 of 1

Default Style

	Untitled 1 - LibreOffice Writer
File Edit	t View Insert Format Styles Table Form Tools Window Help
E . (
Defaul	tstyle 💽 🛞 Veration Seri 💌 😰 🔹 🖉 🤮 🖓 💩 ⊈ 💆 🖓 🖓 🖉 🖉 🐨 🐨 🖉
•	<u> </u>
	7
	We have to use the impact and thermal printer manufactured by professional DOC resaint printer
	company!
	Welcome to use the impact and thermal printer manufactured by professional POS receipt printer
	company!
	Welcome to use the impact and thermal printer manufactured by professional POS receipt printer
	company!
	Welcome to use the impact and thermal printer manufactured by professional POS receipt printer
	company!

		P	rint	_	8	
	General	LibreOffice Writer	Page Layout	Options		
	Printer					
	Print to File					
	XP-80-	USB				
210 mm		he lle				
5 m	De	calls			Properties	
~	Range a	ind Copies				
O All pages				Number of co	pies 1 – +	
	O Pages 1			Collate	-53 -53	
Selection				Conace		
Print in reverse page order						
1/1	Comm	ents None (docur	nent only)	•		
Нер					OK Cancel	

English (UK)

1×101 1

Above is the entire Linux driver installation manual.